

B230CBULLDOZER

B230C SPECIFICATIONS >>>

Cummins QSNT-C240
EFI turbocharged, 4-stroke
Tier 3 / China III
14 L
2,200 rpm
179 kW (240 hp / 243 ps) @ 2,000 rpm
1,050 N·m @ 1,400 rpm
≤217 g/kW·h
24V
225 kN

UNDERCARRIAGE	
Туре	Splayed oscillating, equalizer suspension
Track Shoes (Each Side)	7
Top Idlers (Each Side)	2
Track Type	Single grouser
Shoe Width	560 mm
Track Shoes (Each Side)	39
Link Pitch	216 mm
Gradeability	30°
Ground Pressure	76 kpa


DIMENSIONS	
A Overall Length	5,500 mm
B Height to Top of Cab	3,380 mm
C Track Length on Ground	2,840 mm
D Blade Height	1,395 mm
E Blade Width	3,725 mm
F Width over Track	2,560 mm
G Track Gauge	2,000 mm

-	A	

TRAVEL SPEED		
Forward	Gear 1	0-3.8 km/h
	Gear 2	0-6.9 km/h
	Gear 3	0-12 km/h
Reverse	Gear 1	0-4.9 km/h
	Gear 2	0-8.6 km/h
	Gear 3	0-13.8 km/h
	Gear 3	0-13.8 km/h

HYDRAULIC SYSTEM	
Flow	198 L/min
Pressure	19.5 MPa
Pump	Gear pump
Cylinders	Dual-acting piston type

DRIVE SYSTEM	
Torque Converter	Single-stage, single-phase three elements
Transmission	Planetary power shift
Clutch	Multiple - disc oil powder metallurgy disc compressed by spring, released by hydraulic.
Brakes	Oil two direction floating band brake operated by mechanical foot pedal.



Specifications and design are subject to change notice. Machines shown may include optional equipment. LiuGong standard and optional equipment may vary from region to region. Please consult your LiuGong dealer for infomation specific to your area. Engine power kW is converted to horsepower (1 kW=1.3596 ps and 1 kW=1.3410 hp) in this file.

Head Office

Telp: +62-821-2790-0894 Email: admin.service@bctn.co.id

Komplek Pemuda City Walk Blok B No.30, Jalan Pemuda, Kota Pekanbaru, Riau 28291