



SIX-CYLINDER COMMON-RAIL DIESEL

FULL HYDRAULIC DRIVE SYSTEM

NET PRODUCTIVITY >15 T/H

WHEEL TYPE SUGARCANE HARVESTER

AC60H

Head Office

WTC Mangga Dua, Lantai 3A, Jl. Mangga Dua Raya No. 8,
Kel. Ancol, Kec. Pademangan, Jakarta Utara, 14430.
Telp. (021) 3001 2318 ext 201

Branch Office

- Jakarta
- Pekanbaru
- Surabaya
- Jambi
- Medan





WHEEL TYPE SUGARCANE HARVESTER AC60H

In the process of harvesting sugarcane in the crushing season, are you often at a loss because of the shortage of driving force due to stranding and skidding in the complicated terrain of the sugarcane field, and wasting the harvesting time, or are you distressed because of the high cost brought by the fuel consumption? This time, Zoomlion's sugarcane harvester AC60H, which is equipped with the intelligent harvesting mode, will bring you into the era of intelligent harvesting!

PRODUCT CHARACTERISTICS

Excellent Performance, Intelligent And Convenient

- Equipped with 190hp (up to 210HP) Yuchai six-cylinder high-pressure common rail engine;
- Adopting wheeled walking, fast turnaround speed is perfectly adapted to the sloping land below 10° and 1.2m upper row spacing operation;
- Adopting automatic reducer conveying technology, preventing cane extrusion injury and conveying blockage;
- Cylinder structure fan, axial fan with hydraulic motor drive, with a strong upward airflow to remove sugarcane impurities;
- Slitter system includes a flick disk and a movable knife disk, equipped with a safety limiting device for the cutter;
- Bi-directional screw structure holding device, adapting to the different posture of fallen sugarcane.
- The whole vehicle is controlled by software, real-time data monitoring, and fault diagnosis is visualized and intelligentized;
- Equipped with "idling" function, which effectively reduces fuel consumption;
- Intelligent adjustment of cooling fan according to the ambient temperature.

Excellent Performance, Intelligent And Convenient

- The one-touch operation of the hydraulic motor of the whole vehicle makes the operation of the feeding and unloading systems as convenient as your hands and feet;
- The hydraulic handle controls the entire vehicle transmission, making it easier to move forward/backward and seamlessly switch between high and low speeds;

PARAMETER	SPESIFIKASI
Product Size (LxWxH)	11000 x 2290 x 4800 mm
Weight	9400 kg
Engine Brand	Yuchai
Engine Type	In-line 6 Cylinder
Engine Displacement	6.87 L
Engine Power (Rated)	140 kW (Max 155 kW)
Rotation Speed	2200 r/min
Fuel Capacity	180 L
Front Track	1600 mm
Rear Track	1610 mm
Driving Speed	0–18 km/h
Ground Clearance	260 mm
Row Spacing	≥1200 mm
Suitable Ridge Height	0–200 mm
Suitable Slope	≤10 %
Feeding Capacity	≥6 kg/s
Net Work Hour Productivity	>15 t/h
Loss Rate	≤7 %
Impurity Rate	≤8 %
Hydraulic Oil Capacity	180 L

- Curved design front glass and adjustable seat make it more comfortable to sit while having a wide view;
- High-end load-sensitive hydraulic system, automatic control of flow distribution, to meet the dynamic demand of the whole machine load;
- The electrical components of the whole vehicle are selected from the industry's leading suppliers, waterproof, dustproof and anti-loosening, and the quality of the wiring harness is guaranteed.



Air Suspension Seats



Adjustable Steering Column



Fluid Level Indicator



Equipped with Tailgate Monitoring Device



Hydraulic Tailgate/
Rotary Hopper



BCTN INTELLIGENCE EXCLUSIVE INTERFACE